



Ledinaire Batten

BN013C LED5S/830 L300

830 warm white

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable – just what you need. Both integrated (BN012C) and TLED-based (BN060C) versions are available

Product data

General Information		Number of products on MCB of 16 A type B	
Beam angle of light source	- °		10
Light source color	830 warm white	EU RoHS compliant	Yes
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Unified glare rating CEN	26
Light source replaceable	No	Operating and Electrical	
Number of gear units	1 unit	Input Voltage	220 to 240 V
Driver/power unit/transformer	Power supply unit	Input Frequency	50 or 60 Hz
Driver included	Yes	Initial CLO power consumption	- W
Optic type	Very wide beam	Average CLO power consumption	- W
Luminaire light beam spread	154°	Inrush current	4.54 A
Control interface	-	Inrush time	0.036 ms
Connection	Push-in connector 2-pole	Power Factor (Min)	0.8
Cable	-	Controls and Dimming	
Protection class IEC	Safety class II	Dimmable	No
Glow-wire test	Temperature 650 °C, duration 30 s	Mechanical and Housing	
Flammability mark	For mounting on normally flammable surfaces	Housing Material	Polycarbonate
CE mark	CE mark	Reflector material	Polycarbonate
ENEC mark	-	Optic material	Polycarbonate
Warranty period	3 years		
Constant light output	No		

Ledinaire Batten

Optical cover/lens material	Polycarbonate
Fixation material	-
Optical cover/lens finish	Opal
Overall length	312 mm
Overall width	30 mm
Overall height	36.5 mm
Color	White
Dimensions (Height x Width x Depth)	37 x 30 x 312 mm (1.4 x 1.2 x 12.3 in)

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	475 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	≥80
Initial chromaticity	0.4282, 0.3979, SDCM≤5
Initial input power	5 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life	7.50 %
	50000 h


Lumen maintenance at median useful life*	L65
	50000 h

Application Conditions


Ambient temperature range	-20 to +35 °C
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Not applicable

Product Data

Full product code	871016334953499
Order product name	BN013C LED5S/830 L300
EAN/UPC - Product	8710163349534
Order code	911401835880
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	911401835880
Net Weight (Piece)	0.110 kg



Dimensional drawing



Batten BN060C

Ledinaire Batten

