



MSD

MSD 250/2 30H 1CT/4

These single ended, compact lamps enable optimal light collection and accurate beam control, while they also provide true daylight color temperatures – all to create great stage brightness and vivid entertainment. And since they offer long lifetime usage they help minimize the cost of ownership via fewer lamp replacements and fewer maintenance man hour costs.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Product data

General Information		Operating and Electrical	
Cap-Base	GY9.5 [GY9.5]	Power (Nom)	250 W
Operating Position	UNIVERSAL [Any or Universal (U)]	Lamp Current (Nom)	3 A
Main Application	Studio/Disco	Ignition Supply Voltage (Min)	207 V
Life to 50% Failures (Nom)	3000 h		
System Description	-		
Light Technical		Controls and Dimming	
Color Code	850 [CCT of 5000K]	Dimmable	No
Luminous Flux (Min)	16000 lm		
Luminous Flux (Nom)	18000 lm	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	289	Cap-Base Information	-
Chromaticity Coordinate Y (Nom)	305		
Correlated Color Temperature (Nom)	8100 K	Luminaire Design Requirements	
Luminous Efficacy (rated) (Nom)	72 lm/W	Bulb Temperature (Max)	500 °C
Color Rendering Index (Nom)	70	Pinch Temperature (Max)	350 °C
Product Data			
Full product code	871829122806600		

Order product name	MSD 250/2 30H 1CT/4
EAN/UPC - Product	8718291228066
Order code	928099005115
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

Material Nr. (12NC)	928099005115
Net Weight (Piece)	0.030 kg

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSD 250/2	23 mm	5.0	54 mm	56 mm	55	108 mm	29 mm	28	27 mm
30H 1CT/4		mm			mm		mm		mm

MSD 250/2 30H

Photometric data

