

PRODUCT DATASHEET

SL AREA SPD SM V 30W 740 RV20ST GY

STREETLIGHT AREA SMALL RV20ST | Fitting a broad range of street and area lighting applications



Areas of application

- Outdoor use (IP66)
- M-, C- and P-class roads acc. to EN 13201
- Car parks
- Area lighting

Product benefits

- Functional and minimalistic design
- Low maintenance and operation costs due to long lifetime of LED
- 5 years guarantee

Product features

- Light distributions optimized for streets of similar width to the pole height
- Spigot included, suitable for 48...60 mm diameter poles
- Adjustable spigot for both side-entry and post-top installation
- +/- 30° tilt angle adjustment without opening the housing
- High luminous efficacy: up to 135 lm/W
- Operating temperature: -30...50 °C
- High surge protection: up to 10 kV (L/N-PE)




TECHNICAL DATA

Electrical data

| | |
|--|-----------------------|
| Nominal wattage | 30.00 W |
| Nominal voltage | 100...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 135.000 mA |
| Inrush current | 8.9 A |
| Inrush current time T_{h50} | 100 μ s |
| Max. no. of lum. on circuit break. B16 A | 88 |
| Max. no. of lum. on circuit break. C10 A | 55 |
| Max. no. of lum. on circuit break. C16 A | 82 |
| Power factor λ | > 0.90 |
| Total harmonic distortion | < 20 % |
| Protection class | I |
| Operating mode | Integrated LED driver |


Photometrical data

| | |
|--|----------------------|
| Luminous flux | 4050 lm |
| Luminous efficacy | 135 lm/W |
| Color temperature | 4000 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | 70 |
| Standard deviation of color matching | < 5 sdc _m |
| Low flicker | Yes |
| Photobiological safety group acc. to EN62778 | RG1 |
| Photobiological safety group acc. to EN62471 | RG1 |
| Beam angle | 58° x 160° |



Dimensions & Weight

| | |
|----------------|-----------|
| Length | 448.00 mm |
| Width | 172.00 mm |
| Height | 73.00 mm |
| Product weight | 1450.00 g |
| Cable length | 500 mm |



Materials & Colors

| | |
|--|--------------------|
| Product color | Gray |
| Housing color | Gray |
| Body material | Aluminum |
| Cover material | Polycarbonate (PC) |
| Light emitting surface material | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |

Application & Mounting

| | |
|--|---------------------|
| Ambient temperature range | -30...+50 °C |
| Temperature range at storage | -30...+80 °C |
| Type of connection | Cable, 3-pole |
| Type of protection | IP66 |
| Protection class IK (shock resistance) | IK08 |
| Dimmable | No |
| Mounting type | Side entry post top |
| Mounting location | Pole |
| Application environment | Outdoor |
| Adjustable | Yes |

| | |
|------------------------|-----------------|
| LED module replaceable | Not replaceable |
| With light source | Yes |

Lifespan

| | |
|----------------------------|----------|
| Lifespan L70/B50 at 25 °C | 100000 h |
| Lifespan L80/B10 at 25 °C | 88000 h |
| Lifespan L90/B10 at 25 °C | 44000 h |
| Number of switching cycles | 100000 |

Control gear

| | |
|-----------------------------|--------|
| Output current | 160 mA |
| ECG - Output ripple current | < 5 % |

Certificates & Standards

| | |
|--|--------------------------|
| Standards | CE / REACH / RoHS / ENEC |
| Luminaire with limited surface temperature, "D sign" | No |
| Ball shot safe | No |

DOWNLOAD DATA

Documents and certificates



User instruction



Packaging insert



Declarations Of Conformity CE



Certificates



Declarations Of Conformity UKCA

Photometric and lighting design files



IES file (IES)



LDT file (Eulumdat)

Photometric and lighting design files




LDC typ polar

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854030314 | Folding box 1 | 368 mm x 117 mm x 170 mm | 1792.00 g | 7.32 dm ³ |
| 4099854030321 | Shipping box 4 | 493 mm x 211 mm x 347 mm | 7167.00 g | 36.10 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.