

Fișă tehnică produs

Specificatii



Noua Unica, Rama Unica Pro 8m alb



NU411818

Principal

Gama	Noua Unica
aplicatie a dispozitivului	Montare
Tip produs sau componenta	Rama decorativa
denumire	Unica Pro
numar de posturi	1 post
directie de instalare	Orizontal
tip rama	Simpla
numar module	8 module
mod de fixare	Clipsare
culoare	Alb (RAL 9003)

Suplimentar

Material	Termoplastic stabilizat ABS-UV: rama decorativa Policarbonat: placa intermediara
standarde	IEC 60884-1 SR EN 60669-1
latime	227 mm
inaltime	85 mm
adancime	10 mm
greutate neta	0,036 kg
rezistenta la agenti chimici	Rezistent la alcool (70%) Rezistent la alcool (96%) Rezistent la acid A-lactic Rezistent la amoni cuaternar diluat Rezistent la inalbitor diluat Rezistent la amoniac diluat Rezistent la apa cu sapun Rezistent la detergent de cristal Rezistent la peroxid de hidrogen 10 volume Rezistent la hexan

Mediu

grad de protectie IK	IK04
grad de protectie IP	IP21 D

Unitati de ambalare

Unitate de masura pentru prima forma de impachetare	PCE
---	-----

Numar unitati in prima forma de impachetare	1
Inaltime prima forma de impachetare	1,000 cm
Latime prima forma de impachetare	8,500 cm
Lungime prima forma de impachetare	23,000 cm
Greutate prima forma de impachetare	39,000 g
Unitate de masura pentru a doua forma de impachetare	BB1
Numar unitati in a doua forma de impachetare	5
Inaltime a doua forma de impachetare	5,500 cm
Latime a doua forma de impachetare	11,000 cm
Lungime a doua forma de impachetare	25,000 cm
Greutate a doua forma de impachetare	254,000 g
Unitate de masura pentru a treia forma de impachetare	S04
Numar unitati in a treia forma de impachetare	150
Inaltime a treia forma de impachetare	30,000 cm
Latime a treia forma de impachetare	40,000 cm
Lungime a treia forma de impachetare	60,000 cm
Greutate a treia forma de impachetare	8,233 kg

Garantie contractuala

Garantie	18 luni
----------	---------

