


LED Spotlight

LED Spotlight for defined accent lighting. Radiation angle 38° for retail applications and exhibitions. Total luminous flux: 1400 lm
 Luminaire input power: 15 W. Luminaire efficacy: 94 lm/W. Lifetime: 50.000 h@ L70. Colour rendering Ra >90, colour temperature 3000 K, Chromaticity tolerance (initial MacAdam): 3. 3-phase universal track adapter. Spotlight rotatable through 350° and tiltable through 90°. Housing with integrated converter made of die-cast aluminium, colour white (RAL 9016). Dimensions: 110 x 54 x 154 mm, weight: 0.32 kg.




TE_LUCA_F_S_PERSP.jpg



TE_LUCA_M_S.wmf

Light Distribution

STD - standard



TE_LUCA_S_38°_930.ltd

- Light Source: LED
- Luminaire luminous flux*: 1404 lm
- Luminaire efficacy*: 94 lm/W
- Colour Rendering Index min.: 90
- Correlated colour temperature: 3000 Kelvin
- Chromaticity tolerance (initial MacAdam): 3
- Rated median useful life*: L70 50000h at 25°C
- Ballast: 1x LED_Con
- Luminaire input power*: 15 W Power factor = 0.52
- Dimming: Fixed output
- Total harmonic distortion (THD): 18.00 %

This product contains a light source of energy efficiency class E.

All values marked with an * are rated values. Luminous flux and connected electrical load are subject to an initial tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.