



## Q-LINE CL

**LED Indoor surface-mounted ceiling light, 2m, BAP, black, 3000K**

The Q-LINE ceiling light is optionally available with a white, black, or silver-grey luminaire housing. It is also available with a pure white or warm white LED, and different dimensions. Its high luminance and UGR value of less than 10 make the Q-Line luminaire suitable for workstations. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.

## TECHNICAL DATA

Item no.	1000692
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Level of inrush current	30 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.08
Lumen	4200 lm
Colour temperature	3000 Kelvin
Color	black
CRI	90
UGR ≤	10
LXXBXX data	L70B50
Service life	25000 h
Light distribution	axis symmetric
Light outlet	direct

## Light Source

916433	
--------	---

<b>Length</b>	200 cm
<b>Width</b>	6 cm
<b>Height</b>	6 cm
<b>Net weight</b>	4.171 kg
<b>Gross weight</b>	4.907 kg
<b>BIG WHITE Page</b>	265