




ESKINA

Outdoor surface-mounted wall and ceiling light, anthracite, 3000/4000K, IP65, dimmable

A new family in the SLV lighting world! We are providing you with an integrated outdoor lighting solution with the ESKINA family. Regardless of whether it is a floor stand, a wall and ceiling light or a display fitting. You will find the right light for any application. All of the luminaires can be operated with 3000 K or 4000 K. Versions with motion sensors are also available.



TECHNICAL DATA

| | |
|----------------------------|-------------------------|
| Item no. | 1002903 |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 65 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Surface |
| Assembly details | Ceiling,Wall |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Number of through-wires | 20 |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 350 mA |
| Safety class | I |
| Wattage | 14.5 W |
| Ambient temperature | 25 °C |
| Level of inrush current | 30 A |
| Duration of inrush current | 40 µs |
| Stroboscopic effect (SVM) | 0.05 |
| Lumen | 1000 lm |
| Colour temperature | 3000/4000 Kelvin |
| Beam angle | 95 ° |
| Color | anthracite |

Light Source

| | |
|--------|-----------------------------------------------------------------------------------|
| 916405 |  |
|--------|-----------------------------------------------------------------------------------|

| | |
|---------------------------|----------------------|
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 36000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Height | 22.3 cm |
| Diameter | 13.8 cm |
| Net weight | 1.248 kg |
| Gross weight | 1.549 kg |
| BIG WHITE Page | 807 |