




3~ NUMINOS® PHASE S

3 phase system light black/black 3000K 36°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the 3~ NUMINOS® PHASE S 3-phase system light LED, which convinces with best workmanship and light quality. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 10.42 watts, luminous flux of 1020 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



TECHNICAL DATA

| | |
|----------------------------|---------------------------|
| Item no. | 1004083 |
| Rotating or tilting | rotary Bar and tiltable |
| Assembly details | Track Ceiling, Track Wall |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 250 mA |
| Safety class | I |
| Wattage | 10.42 W |
| Level of inrush current | 13 A |
| Duration of inrush current | 8 µs |
| Lumen | 1020 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 36 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 13 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 16.2 cm |
| Height | 14.5 cm |

Light Source

| | |
|--------|---|
| 791815 |  |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006167 | NUMINOS® S , white front ring |
|---------|-------------------------------|

| | |
|----------------|----------|
| Diameter | 6.5 cm |
| Net weight | 0.51 kg |
| Gross weight | 0.832 kg |
| BIG WHITE Page | 62 |