



NUMINOS® CL PHASE M

Indoor LED surface ceiling light black/black 3000K 24°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® CL PHASE M indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or for illuminating larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1955 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1004226
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20.1 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Number of luminaires at LS B16A	50
Number of luminaires at LS C16A	85
Level of inrush current	13 A
Duration of inrush current	30 µs
Lumen	1955 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L80B50

Light Source

791822	
--------	---

Accessories

1006168	NUMINOS® M , white front ring
---------	-------------------------------

Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	18.5 cm
Diameter	8.5 cm
Net weight	0.68 kg
Gross weight	0.93 kg
BIG WHITE Page	104