




## NUMINOS® SPOT PHASE L

Indoor LED recessed ceiling light black/black 3000K 60°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® SPOT PHASE L indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2400 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



### TECHNICAL DATA

<b>Item no.</b>	1004300
<b>Rotating or tilting</b>	rotary Bar and tiltable
<b>Assembly</b>	Surface
<b>Assembly details</b>	Ceiling
<b>Dimmable</b>	Yes
<b>Dimming technology</b>	trailing edge
<b>Primary nominal voltage</b>	220-240V ~50/60Hz
<b>Secondary power / voltage</b>	700 mA
<b>Safety class</b>	I
<b>Wattage</b>	28 W
<b>Minimum ambient temperature</b>	-20 °C
<b>Maximum ambient temperature</b>	30 °C
<b>Number of luminaires at LS B16A</b>	34
<b>Number of luminaires at LS C16A</b>	58
<b>Level of inrush current</b>	6 A
<b>Duration of inrush current</b>	40 µs
<b>Lumen</b>	2400 lm
<b>Colour temperature</b>	3000 Kelvin
<b>Beam angle</b>	60 °
<b>Color</b>	black
<b>CRI</b>	90
<b>UGR ≤</b>	22

## Light Source

791822	
--------	---

## Accessories

1006169	NUMINOS® L , white front ring
---------	-------------------------------

LXXBXX data	L80B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Length	21.3 cm
Height	18 cm
Diameter	10 cm
Net weight	1.08 kg
Gross weight	1.425 kg
BIG WHITE Page	101