




## NUMINOS® SPOT DALI M

## Indoor LED recessed ceiling light black/black 3000K $60^\circ$

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® SPOT DALI M indoor ceiling-mounted light LED, which impresses with its high-quality work-manship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1880 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



## **TECHNICAL DATA**

| Item no.:                                | 1004492                |  |
|--|------------------------|--|
| Primary nominal voltage                  | 220-240V ~50/60Hz mA/V |  |
| Secondary power / secondary volta-<br>ge | 500mA                  |  |
| Length                                   | 18.5 cm                |  |
| Height                                   | 16.5 cm                |  |
| Diameter                                 | 8.5 cm                 |  |
| Net weight                               | 0.89 kg                |  |
| Gross weight                             | 1.19 kg                |  |
| Safety class                             | 1                      |  |
| Assembly                                 | Surface                |  |
| Assembly details                         | Ceiling                |  |
| Dimmable                                 | Yes                    |  |
| Dimming technology                       | DALI                   |  |
| Wattage                                  | 20.1 W                 |  |
| Lumen                                    | 1880 lm                |  |
| Colour temperature                       | 3000 Kelvin            |  |
| Beam angle                               | 60 °                   |  |
| Color                                    | black                  |  |
| CRI                                      | 90                     |  |
| UGR≤                                     | 22                     |  |
| LXXBXX data                              | L80B50                 |  |
| Service life                             | 50000 h                |  |
|  |                        |  |



## Light Source

| 791822      | A E                           | BIG WHITE Page | 74 |
|-------------|-------------------------------|----------------|----|
| Accessories |                               |                |    |
| 1006168     | NUMINOS® M , white front ring |                |    |