


3~ NUMINOS® DALI L

3 phase system light black/black 3000K 36°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the 3~ NUMINOS® DALI L 3-phase system light LED, which impresses with its high-quality workmanship and light. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 28 watts, luminous flux of 2340 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| | |
|-----------------------------|-------------------------|
| Item no. | 1004563 |
| Rotating or tilting | rotary Bar and tiltable |
| Assembly details | Track Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 28 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Level of inrush current | 30 A |
| Duration of inrush current | 2 µs |
| Lumen | 2340 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 36 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 13 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Light distribution | rotational symmetric |

Light Source

| | |
|--------|---|
| 791822 |  |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|

| | |
|----------------|----------|
| Light outlet | direct |
| Risk Group | 1 |
| Length | 21.3 cm |
| Height | 18 cm |
| Diameter | 10 cm |
| Net weight | 1.115 kg |
| Gross weight | 1.45 kg |
| BIG WHITE Page | 66 |