




NUMINOS® XL PHASE

black 3-phase spot, 36W 4000K 36°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® XL PHASE 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3760 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1005736
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	30 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	3760 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR ≤	19
Risk Group	1

Light Source

791850	
--------	-----------------------------------------------------------------------------------

Length	25.8 cm
Height	20 cm
Diameter	12 cm
Net weight	1.63 kg
Gross weight	2 kg
BIG WHITE Page	69