




NUMINOS® XL PHASE

white / black 3-phase spot, 36W 4000K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® XL PHASE 3-phase system light LED, which convinces with best workmanship and light quality. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3760 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1005739
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	30 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	3760 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	white
CRI	90
UGR ≤	19
Risk Group	1

Light Source

791850	
--------	-----------------------------------------------------------------------------------

Length	25.8 cm
Height	20 cm
Diameter	12 cm
Net weight	1.63 kg
Gross weight	2 kg
BIG WHITE Page	69