



DASAR FLAT 120 EL

stainless steel in-ground light, 7W 4000K

The DASAR FLAT 120 EL is the high-voltage recessed ground light from SLV that can be walked on and impresses with its stainless steel screen and glass cover in a partial satin finish. The LED outdoor recessed ground light creates an exciting lighting atmosphere and impresses with a long LED lifespan of 30,000 hours. When will you test out the benefits of SLV's impressive outdoor lights?

TECHNICAL DATA

Item no.	1006107
IP Code	IP 65 / IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Mechanical loading	0.5 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Operating efficiency (LOR)	0,5
Number of luminaires at LS B16A	112
Number of luminaires at LS C16A	200
Level of inrush current	10 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.4
Lumen	540 lm
Colour temperature	4000 Kelvin
Color	stainless steel

Light Source

916484	
--------	---

CRI	80
LXXBXX data	L70B50
Service life	30000 h
Risk Group	1
Depth	8 cm
Diameter	12 cm
Net weight	0.721 kg
Gross weight	0.813 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	10.6 cm
BIG WHITE Page	839