



FLOODI M

anthracite / transparent wall and ceiling-mounted light,
30W 3000K 100°

High-output FLOODI spotlight for effective illumination of areas and squares. The swivelling mounting bracket and IP65 protection make the spotlight suitable for outdoor mounting on walls and ceilings. The spotlight is connected electrically through the existing cable connector on the casing itself.

TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 1006192 |
| Rotating or tilting | tiltable |
| IP Code | IP 65 |
| Impact resistance class | IK 06 |
| Impact resistance | 1 Joule |
| Assembly | Surface |
| Assembly details | Ceiling,Wall |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Safety class | I |
| Wattage | 30 W |
| Minimum ambient temperature | -30 °C |
| Maximum ambient temperature | 35 °C |
| Stroboscopic effect (SVM) | 0.04 |
| Lumen | 2980 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 100 ° |
| Color | anthracite |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 50000 h |
| Length | 16 cm |
| Width | 2.8 cm |

Light Source

| | |
|--------|---|
| 954804 |  |
|--------|---|

Accessories

| | |
|---------|-------------------|
| 1006326 | Sensor for FLOODI |
|---------|-------------------|

| | |
|----------------|----------|
| Height | 22.3 cm |
| Net weight | 0.542 kg |
| Gross weight | 0.698 kg |
| BIG WHITE Page | 691 |