




ROCCI 125

outdoor inground fitting, LED, 3000K, IP67, round, stainless steel 316, max. 6W

The inground fitting ROCCI 125 has a round stainless steel shade with a transparent glass cover and is fitted with a COB LED module. With protection class IP67, the luminaire is available with two shapes of shades and is suitable for outdoor use. The electrical connection is made directly to the 230V mains supply. A mounting pot is included in the delivery for simple assembly.



TECHNICAL DATA

| | |
|---------------------------------------|-------------------|
| Item no. | 227600 |
| IP Code | IP 67 |
| Impact resistance class | IK 08 |
| Impact resistance | 5 Joule |
| Assembly | Recessed |
| Assembly details | Ground |
| Primary nominal voltage | 100-277V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 8.6 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Level of inrush current | 5 A |
| Duration of inrush current | 25 µs |
| Temperature at glass (light emission) | 48 °C |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 580 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 120 ° |
| Color | stainless steel |
| LXXBXX data | L70B50 |
| Service life | 40000 h |

Light Source

| | |
|--------|---|
| 916530 |  |
|--------|---|

| | |
|------------------------------|----------|
| Depth | 12.7 cm |
| Diameter | 12.6 cm |
| Net weight | 0.924 kg |
| Gross weight | 1.078 kg |
| Shape of cut-out | round |
| Installation depth | 12.3 cm |
| Installation diameter | 11.3 cm |
| BIG WHITE Page | 854 |