




DASAR 215

outdoor inground fitting, TC-(D,H,T,Q)SE, IP67, round, stainless steel 316, max. 80W

The high-voltage DASAR 215 UNI inground light is accessible and impresses with its stainless steel screen and glass cover in a partial satin finish. With its IP 67 protection class, it is optimally suited for outdoor use. Thanks to the pivoting E27 fitting, direct the light cone individually. The housing is made of high-quality 316 stainless steel and glass. When will you test out the benefits of SLV's impressive outdoor lights?



TECHNICAL DATA

| Item no. | 229200 |
|-------------------------|-------------------|
| Socket | E27 |
| Number of sockets | 1 |
| IP Code | IP 67 |
| Impact resistance class | IK 08 |
| Impact resistance | 5 Joule |
| Assembly | Recessed |
| Assembly details | Ground |
| Mechanical loading | 2 t |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Safety class | I |
| Wattage | 11 W |
| Color | stainless steel |
| Light distribution | symmetric |
| Light outlet | direct |
| Depth | 22.5 cm |
| Diameter | 21.5 cm |
| Net weight | 3.397 kg |
| Gross weight | 4.222 kg |
| Shape of cut-out | round |
| Installation depth | 28.3 cm |
| Installation diameter | 20 cm |
| | |



| BIG WHITE Page | 847 |
|----------------|-----|
|----------------|-----|

Recommended lamp

| T38 E27 , white LED light, 8W 3000K CRI90 240° |
|---|
| |