



DASAR® 920

HV, LED outdoor inground fitting, LED, 3000K, IP67, round, bezel brushed stainless steel, 230V, 5,6W

The DASAR LED HV recessed ground light can be walked on and impresses with its stainless steel screen and glass cover in a partial satin finish. In this way, the outdoor LED recessed ground light creates an exciting lighting atmosphere that impresses with a long LED lifespan of 25,000 hours. Experience light with SLV – your innovative partner for all kinds of outdoor lighting for 40 years.

TECHNICAL DATA

Item no.	233520
IP Code	IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Mechanical loading	1 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	400 mA
Safety class	I
Wattage	5.5 W
Maximum ambient temperature	40 °C
Temperature at glass (light emission)	44.8 °C
Lumen	300 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	stainless steel
CRI	80
LXXBXX data	L70B50
Service life	25000 h
Light distribution	rotational symmetric
Light outlet	direct

Light Source

916428	
--------	---

Depth	9.4 cm
Diameter	9.2 cm
Net weight	0.704 kg
Gross weight	0.788 kg
Shape of cut-out	round
Installation depth	10.2 cm
Installation diameter	8.2 cm
BIG WHITE Page	840